



Brunette Flare Butt Reducer

*Eliminate Feeding problems inside and outside the mill.
Each and every machine center in your mill will get relief!*

Realize these KEY BENEFITS:

- Cleaner chips because of elimination of bark inclusions in the flare butt
- Improved productivity
- Increased recovery because of more accurate scanning and log positioning
- Reduced downtime



Go from this...



Through the Butt Reducer...

BRUNETTE FLARE BUTT REDUCER Model # FBR4020

TECHNICAL SPECIFICATIONS

Capacity:	6/7 logs/min. (based on 24" diameter log)
Maximum removal:	4" radially per rotation
Maximum log diameter:	40" ϕ log with 54" ϕ butt
Minimum log length:	8'-6"
Maximum log length:	20'-0" (up to tree length)
Cutterhead:	10" ϕ x 52" long
Cutting Tools:	Four sided
Number of cutting tools:	44
Main motor:	100 HP, 1800 RPM
Log turner drive - Bottom:	One (1) gear motor, 5 HP single speed
Log turner drive - Top:	One (1) gear motor, 5 HP single speed
Hydraulic unit:	25 HP, 1800 RPM
Weight including main motor:	Approx 18,000 lbs.

To **THIS**, IN SECONDS!



VK Brunette, Inc.

115 Brunet Way
Ball Ground, GA 30107

Phone: (770) 345-1400
FAX: (770) 345-6191